

# Seismic Risk Mitigation in Palestine

Funded by



European Commission



Project full title:

**" Support Action for Strengthening Palestinian-administrated Areas capabilities for Seismic Risk Mitigation "**



**An-Najah National University  
Urban Planning and Disaster Risk Reduction Center**

Supported by:



Jalal Al Dabbeek, An Najah  
National University




**Istituto Universitario di Studi Superiori  
)IUSS(di Pavia**

31/07/2013


# RETROFITINGT

**ONE-SIDED JACKETING OF COLUMNS**




1 - existing column; 2 - jacket; 3 - existing reinforcement;  
4 - added longitudinal reinforcement; 5 - added ties;  
6 - welding; 7 - bunt bars

**ALTERNATIVES FOR  
JACKETING OF COLUMNS**



1 - existing column; 2 - beam; 3 - existing column; 4 - jacket;  
5 - added longitudinal reinforcement; 6 - added ties


**FOUR-SIDED JACKETING OF  
COLUMNS**



- 1 - existing column
- 2 - jacket
- 3 - key
- 4 - bunt base
- 5 - added reinforcement
- 6 - ties
- 7 - welding
- 8 - alternative corners

### STEEL PROFILE JACKETING

1. Steel profile jacketing consists of four longitudinal angle profiles placed one at each corner of the existing reinforced concrete column and connected together in a skeleton with transverse steel straps.
  2. Laterals are welded to the angle profiles and can be either rebars of minimum 13 mm diameter or steel straps of minimum size 25/4 mm.
  3. Angle profiles should be no less than L 50x50x5.
  4. Gaps and voids between the angle profiles and the surface of the existing column must be filled with non-shrinking cement grout or resin grout.
  5. A covering with concrete or shotcrete reinforced with welded fabrics is efficient for corrosion or fire protection.
  6. Tight bearing between the angle profiles and the floor structures, essential for load transmitting, is achieved by an angle profile collar formed around the column perimeter in contact with the surfaces of the floor structures.
1. An improvement of the ductile behavior and an increase of the axial load capacity of the strengthened column is achieved.
  2. The stiffness, however, remains relatively unchanged.



Jalal Al Dabbeek, An Najah  
National University  
1 - existing column ; 2 - steel angle profile; 3 - steel plate;  
4 - supporting slab and floor



Jalal Al Dabbeek, An Najah  
National University

31/07/2013

### STEEL ENCASEMENT


Steel encasement is the complete covering of the existing column with thin steel plates. Steel encasement offers the possibility of only a small increase in column size.

Steel plates are continuously welded together and located at a distance from the existing column.

The voids between the encasement and the column should be filled with non-shrinking or expanding cement grout or concrete.

Ductility and axial strength capacity can be considerably increased locally. However, the flexural strength of the frame structure cannot be improved by this method.


Special measures must be provided for fire and corrosion protection.






1 - existing column; 2 - non-shrinking concrete or grout; 3 - steel encasement;  
4 - steel plates

**BEAMS**


The purpose of strengthening deficient beams is to provide adequate strength and stiffness to resist gravity and seismic loads. It is imperative that the rehabilitation procedure does not create strong-beam-weak-column situations.




1 - existing reinforcement; 2 - existing stirrups; 3 - added longitudinal  
4 - added stirrups; 5 - welded connecting bar; 6 - welding; 7 - collar of  
angle profiles



# Shear Walls



# Shear Walls



31/07/2013

**INTRODUCTION OF NEW STRUCTURAL ELEMENTS**


Alternative newly added elements are:

1. Shear walls in a frame or skeleton structure
2. Additional shear walls in a shear wall structure
3. Additional frames in a frame or skeleton structure
4. Bracing (steel or reinforced concrete) in a frame or skeleton structure.

It is important to observe the following:



1. Avoid large concentration of forces in members with small strength and/or ductility capacities by locating the strengthening elements uniformly throughout the structure.
2. Improve the distribution of lateral force by reducing the effects of torsion and irregularities.
3. Provide sufficient strength, stiffness and ductility of the individual elements and of the whole structure.
4. Provide adequate strength in connections between the existing structure and the newly added elements.

# Shear Walls



# Shear Walls


a.



1 - existing wall  
2 - added wall



# Shear Walls

b.





# Shear Walls


c.







# Shear Walls



# Shear Walls



# Infilled Walls









Fig. – Building 10 shear walls  
Jalal Al Dabbeek, An Najah  
National University


31/07/2013

# Shear Walls







- 1 - added shear wall
- 2 - existing structure
- 3 - added concrete
- 4 - added reinforcement
- 5 - added ties
- 6 - dewel
- 7 - added diagonal bars
- 8 - added vertical bars

# Shear Walls




- 1 - added shear wall
- 2 - existing structure
- 3 - added concrete
- 4 - added reinforcement
- 5 - added ties
- 6 - dowel
- 7 - added diagonal bars.
- 8 - added vertical bars






1 - existing wall; 2 - existing slab; 3 - added longitudinal reinforcement; 4 - added wire fabric; 5 - diagonal connecting bars; 6 - added ties




# Diagonal Bracing








# الطابق الرخو


# SOFT-FIRST-STORY BUILDINGS




























# الدرج وسط المبني











































Figure 5.1-2 Wall Enclosure without Roof [1]




Figure 5.1-3 Roofed Wall Enclosure [1]





Figure 4.1-2 Cracking in Shear Wall at Corners of Opening



**Figure 7.1-2** Cracking of Spandrel Wall between opening




Figure 9.1-5 Gable Band and Roof Band in Barrack Type Building [1]




Figure 7.1-1 Cracking in Bearing Wall Building due to Bending and Shear





Figure 9.1-1 Recommendation regarding openings in bearing walls [1]



NOTE : WIDTH OF WIRE MESH  $\geq$  400 mm -

**Figure 9.1.21 Splint and bandage strengthening technique [1]**



Jalal Al Dabbeek, An Najah  
National University

31/07/2013






Jalal Al Dabbeek, An Najah  
National University

31/07/2013





Jalal Al Dabbeek, An Najah  
National University

31/07/2013



Jalal Al Dabbeek, An Najah  
National University



31/07/2013



Jalal Al Dabbeek, An Najah  
National University

31/07/2013





قصور في صيانة وحماية المنشآت

Jalal Al Dabbeek, An Najah  
National University

31/07/2013





سقوط الغطاء الخرساني وظهور

الصدأ في الحديد الرئيسي والكانات

سقوط الغطاء الخرساني نتيجة الصدأ




سقوط بلاطة سقف المصنع نتيجة الصدا وتراكم المياه فوقها .



بقع الصدأ ذات اللون البني

(شرح رأسى (موازى لحدید التسلیح) سببه الصدأ




سقوط الغطاء

الخرسانة للبلاطة بسبب الصدأ

شروخ صدأ الحديد

الطولية الموازية للتسليح السفلي للكمره



انهيار (تصدع) البلاط نتيجة صدأ الحديد  
Jalal Al Dabeeq, An Najah  
National University

31/07/2013

تأثير الأحماض

على الخرسانة السطحية



وصول تأثير

الأحماض إلى صلب التسليح

# ما هو الحل للحماية من هذه المشاكل؟



إزالة الخرسانة بحيث تظهر أسياخ

التسليح لإزالة الصدأ من عليها



إزالة الخرسانة بعمق

Jalal Al Dabbeek, An Najah

National University

كاف خلف أسياخ العامور

31/07/2013



تنظيف صلب التسليح باستخدام الأجهزة الكهربائية

Jalal Al Dabbeek, An Najah  
National University

31/07/2013

# THANKS

موقع المركز:  
جامعة النجاح الوطنية  
مركز التخطيط الحضري والحد  
من مخاطر الكوارث  
[www.najah.edu](http://www.najah.edu)



زوروا:  
موقع تخفيف مخاطر الزلازل في  
فلسطين

[www.sasparm.ps](http://www.sasparm.ps)

[seiscen@najah.edu](mailto:seiscen@najah.edu)

شكراً لحسن اصغائكم